



XTG 75W90 LS

DESCRIPTION

Synthetic oil with a high viscosity index, formulated to lubricate mechanical transmissions and differentials submitted to difficult operating conditions (heavy loads, high speed and temperature).

APPLICATION

BARDAHL XTG 75w90 LS is particularly suitable for heavy loaded hypoid differentials, with « Limited Slip and Auto-Locking ». Provides an excellent stability at different temperatures.

SPECIFICATIONS

This product offers the following performance level:

API	GL5
MIL	MIL-L-2105D
ZF	TE-ML 05C
LIEBHERR	P>1900 mg/kg

PROPERTIES

- ✓ Offers a good resistance to high temperature,
- ✓ Provides very good extreme pressure (EP) properties,
- ✓ Has a low pour point,
- ✓ Provides a high resistance against corrosion and oxidation,
- ✓ Provides anti-wear and antifoam properties,
- ✓ Has a limited slip.

TECHNICAL DATA

Density at 20°C	Kg/l	0,874
Viscosity at 40°C	mm ² /s	78,8
Viscosity at 100°C	mm ² /s	14,40
Viscosity index		192
Flash point COC, °C	°C	172
Pour point, °C	°C	-45

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet. Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

33051	12 x 1 L
33053	3 x 5 L
33054	60 L
33057	205 L