

XTEC 0W20 V

DESCRIPTION

New generation fully synthetic engine oil developed to avoid fuel overconsumption. Formulated from the latest generation performance additives.

APPLICATION

BARD AHL XTEC 0w20 V improves the consumption of the fuel, allows for a higher resistance to shearing. Bardahl XTEC 0w20 V is particularly suitable for Volvo diesel and petrol engines.

SPECIFICATIONS

This product offers the following performance level:

ACEA	C5 / C6
API	SP Resource Conserving
ILSAC	GF-6A
VOLVO	VCC RBS0-2AE
FORD	WSS-M2C947-B1 / WSS-M2C962-A1
JAGUAR LAND ROVER	STJLR.03.5006
MB	229.71 / 229.72
OPEL	OV 040 1547 - A20
CHRYSLER	MS-12145
FIAT	9.55535-GSX

PROPERTIES

- ✓ Avoids fuel overconsumption,
- ✓ Good resistance against shearing,
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Makes cold starting easier even at very low temperature (-40°C),
- ✓ Anti-foam,
- ✓ Anti-wear,
- ✓ Anti-corrosion,
- ✓ High and stable viscosity index.



TECHNICAL DATA SHEET V032023

TECHNICAL DATA

Density at 15°C	Kg/l	0,848
Viscosity at -35°C	mPa.s	6000
Viscosity at 40°C	mm ² /s	42,6
Viscosity at 100°C	mm ² /s	8,61
Viscosity index		186
Flash point COC, °C	°C	224
Pour point, °C	°C	-45
TBN alcalinity	mgKOH/g	7,5
Sulphated ash contents	%	0,8

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling: any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36811	12 X 1L
36813	3 X 5 L
36817	20L
36814	60L
36818	205L