



Auto

→ Workshop consumables

Tyre Sealant

Ref. 4942 (FR)

6x400ml

Ref. 4942B (GB/FR/NL)

6x400ml

Ref. 4943 (ES/IT/BG/GR)

6x400ml

PROPERTIES

- Repairs and reinflates tyre within seconds without tools or dismantling.
- Not suitable for torn tyres, punctures larger than 5mm or on tyre sidewall.
- Suitable for tyres equipped with tube or tubeless.

INSTRUCTIONS FOR USE

1. If possible, remove the object which has caused the puncture and deflate the tyre completely.
2. If possible, move the vehicle so as to position the puncture to the ground.
3. Shake well the aerosol. In cold weather conditions, warm it with your hands or with the passenger heating.
4. Completely screw the tube nozzle without using force.
5. Spray until complete consumption of the product while keeping the aerosol in a vertical position.
6. When the tyre is reinflated, quickly unscrew the nozzle and drive between 10 to 20 km without exceeding a speed of 50km/h, so as to allow the product to be perfectly released.
7. Check and complete the pressure if necessary according to the manufacturer recommendation.



BARD AHL | *NOTHING WILL STOP YOU*
ADDITIVES & LUBRICANTS

SADAPS BARD AHL ADDITIVES & LUBRICANTS

Rue du Mont des Carliers, 3 – ZI Tournai Ouest 2 – B-7522 TOURNAI
T: (+32) (0) 69 59 03 60

www.bardahl.fr

V11/2021