



# XTEC 0W20 R

## DESCRIPTION

New generation 100% synthetic oil, developed to limit fuel overconsumption. Developed to reduce CO<sub>2</sub> emissions and for optimum engine cleanliness. Formulated with the latest generation additives.

## APPLICATION

**BARDAHL XTEC 0w20 R** improves fuel consumption, cleans the pistons, reduces emissions and protects against wear. The XTEC 0w20 R is particularly suitable for vehicles equipped with particulate filter. Caution: RN17 FE specification is not compatible with previous RN0700/RN0710/RN0720/RN17RSA specifications.

## SPECIFICATIONS

This product offers the following performance level:

ACEA	C5
RENAULT	RN17 FE

## PROPERTIES

- ✓ Limits fuel overconsumption,
- ✓ Provides an excellent resistance against 'shearing',
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Contains strong anti-wear, anti-corrosion, anti-foam and anti-oxidation additives,



## TECHNICAL DATA SHEET V032023

### TECHNICAL DATA

Density at 15°C	Kg/l	0,844
Viscosity at -35°C	mPa.s	4920
Viscosity at 40°C	mm <sup>2</sup> /s	40,20
Viscosity at 100°C	mm <sup>2</sup> /s	8,35
Viscosity Index		190
Flash point COC, °C	°C	216
Pour point, °C	°C	-48
TBN Alcalinity	mgKOH/g	8,7
Sulphated Ash contents	%	0,78

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

### RECOMMENDATIONS

**Handling :** any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

**Storage :** it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

### REFERENCES & AVAILABILITIES

35971	12 x 1 L
35973	3 x 5 L
35978	1 x 20 L
35974	1 x 60 L
35977	1 x 205 L