



XTM-M 20w50



DESCRIPTION

BARDAHL XTM-M 20w50 is formulated for 4-stroke motorbike engines with wet or dry clutch.
Ideal for Harley Davidson.

SPECIFICATIONS

This product offers the following performance level:

API	SN and retro compatible with SM, SL, SJ, SH, SG, SF
JASO	MA2

PROPERTIES

- ✓ BARDAHL has selected the best synthetic and mineral bases to develop this semi-synthetic oil.
- ✓ The BARDAHL performance additives used in this formula will guarantee an excellent anti-wear action.
- ✓ Very good stability.
- ✓ Very good friction characteristics.
- ✓ Anti-corrosion and anti-foam properties.
- ✓ Good dispersion and detergency properties.



TECHNICAL DATA SHEET V062022

TECHNICAL DATA

Colour		Amber
Density at 15°C – kg/l	ASTM D1298	0,880
Viscosity at 40°C – mm²/s	ASTM D445	158,82
Viscosity at 100°C – mm²/s	ASTM D445	17,86
Viscosity Index	ASTM D2270	124
Pour point - °C	ASTM D97	-27
TBN – mgKOH/g	ASTM D2896	7,45
Flash point - °C	ASTM D92	234

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet. Always check the manufacturer manual before use. Miscible in other synthetic or mineral 4T motorbike oils.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

35961	12x1L
35962	4x4L
35964	60L
35967	205L