



Green Power Four SAE 10W-40

Product Sheet

Green Power Four is a premium quality lubricant for latest generation 4-stroke outboard petrol engines demanding high performance lubricants with API SN / CF and ACEA A3/B3 requirements.

Superior performance – Total protection

The exclusive Bardahl Polar Plus anti-friction formula forms a lubricating molecular film capable of creating a permanent protective barrier, drastically reducing friction on all engine parts. Bardahl ensures significantly higher performance than conventional lubricants.

- Superior wear control even in presence of strong dilution with petrol.
- Greater durability and cleanliness of all engine parts.
- Protects the engine from corrosion.
- Controls the formation of sludge favored by low operating temperature and humidity.

PERFORMANCE LEVEL

ACEA A3/B4, API SN / CF, MB 229.3, VW 502.00 / 505.00,
Renault RN0700 / RN0710, PSA B71 2300

CHEMICAL-PHYSICAL CHARACTERISTICS

Viscosity at 40°C	95,8 cSt
Viscosity at 40°C	14 cSt
Density at 15°C	0,878 kg/l
Viscosity Index	152
Flash point	210°C
Pour point	-33°C
T.B.N.	9 (mg KOH/g)

Values mentioned in this table are indicative and variable within certain tolerances

STORAGE

Store in the original closed packaging, maintaining it indoors, protected from moisture, direct exposure to sunlight and weather conditions. Avoid continuous and excessive temperature changes.

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio