



# XTS 0W30

## DESCRIPTION

Fully synthetic engine oil formulated with last generation performance additives to reduce friction, eliminate sludge and optimize fuel consumption. Offers a good general protection of the engine.

## APPLICATION

**BARDAHL XTS 0w30** provides excellent performance at low temperature. It has been developed to meet the requirements of the Volkswagen « Longlife 2 » programme. It is a fuel economy engine oil. It is not suitable for engines requiring a VW 503.01 performance level.

## SPECIFICATIONS

This product offers the following performance level:

ACEA	A3/B4
API	SN/CF
MERCEDES BENZ	229.3
VW	503.00/506.00/506.01
BMW	Longlife-01

## PROPERTIES

- ✓ Fuel economy engine oil,
- ✓ Offers a stable viscosity and a high Viscosity Index,
- ✓ Extends the oil drain interval,
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Forms a protective lubricating film at high temperature,
- ✓ Makes cold start easier,
- ✓ Provides a good resistance against « shearing »,
- ✓ Contains anti-corrosion, anti-wear and anti-foam additives.



## TECHNICAL DATA SHEET V032023

### TECHNICAL DATA

Density at 15°C	Kg/l	0,856
Viscosity at -30°C	mPa.s	5580
Viscosity at 40°C	mm <sup>2</sup> /s	53
Viscosity at 100°C	mm <sup>2</sup> /s	9,6
Viscosity Index		165
Flash point COC, °C	°C	215
Pour point, °C	°C	-39
TBN alcalinity	mgKOH/g	10
Sulphated ash contents	%	1,28

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

### RECOMMENDATIONS

**Handling :** any safety information related to the handling and use of this product are gathered in the Safety Data Sheet. Always check the manufacturer car manual before use.

**Storage :** it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

### REFERENCES & AVAILABILITIES

36131	12 x 1 L
36133	3 x 5 L
36134	60 L
36137	205 L