



XTM 20W50

DESCRIPTION

Mineral engine oil for passenger cars and delivery vans. Ideal for multi-fleet applications. Compatible with petrol, diesel and LPG cars, turbo-charged or not and equipped or not with a catalytic converter.

APPLICATION

BARDAHL XTM 20w50 offers excellent cleaning properties and a very good protection against wear thanks to viscosity stabilizing additives. It also provides a good antirust and anticorrosion protection.

SPECIFICATIONS

This product offers the following performance level:

API	SF/CD
-----	-------

PROPERTIES

- ✓ Avoids deposits on pistons.
- ✓ Provides excellent cleaning properties.
- ✓ Offers anti-corrosion properties.



TECHNICAL DATA SHEET V032023

TECHNICAL DATA

Density at 20°C	Kg/l	0,880
Density at 20°C	Kg/l	0,871
Viscosity at -15°C	cP	<9500
Viscosity at 40°C	mm ² /s	153,35
Viscosity at 100°C	mm ² /s	17,98
Viscosity Index		130

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36701	12 x 1 L
36702	4 x 4 L
36703	3 x 5 L
36708	20 L
36704	60 L
36707	205 L