



XTEC 0W30 B12

DESCRIPTION

New generation fully synthetic engine oil developed to avoid fuel overconsumption and extend the lifespan of the DPF. Formulated from last generation performance additives.

APPLICATION

BARDAHL XTEC 0w30 B12 improves the consumption of the fuel, fuel economy and reduces the formation of post-combustion residues. The XTEC 0w30 B12 can be used in any diesel or petrol engine with turbo-charged or not with the following performance level. This oil can be used on vehicles equipped with 3 way-catalytic converters.

SPECIFICATIONS

This product offers the following performance level:

BMW	Longlife-12 FE
ACEA	C2

PROPERTIES

- ✓ Limits fuel overconsumption, « fuel economy »,
- ✓ Reduces the formation of post-combustion residues,
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Makes cold starting easier even at very low temperature,
- ✓ Strong resistance against oxidation,
- ✓ Anti-foam,
- ✓ Anti-wear,
- ✓ Anti-corrosion,
- ✓ High and stable viscosity index,
- ✓ Low SAPS,
- ✓ Safe lubrication film at high temperatures.



TECHNICAL DATA SHEET V032023

TECHNICAL DATA

Density at 15°C	Kg/l	0,841
Viscosity at -35°C	mPa.s	5590
Viscosity at 40°C	mm ² /s	54,60
Viscosity at 100°C	mm ² /s	10,00
Viscosity index		172
Flash point COC, °C	°C	222
Pour point, °C	°C	-45
TBN alcalinity	mgKOH/g	8,3
Sulphated ash contents	%	0,76

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling: any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36841	12 x 1L
36843	3 x 5L
36848	20L
36844	60L
36847	205L