



MULTI ATF 7G

DESCRIPTION: Synthetic high quality automatic transmission fluid, with a very high viscosity index. This fluid is suitable for automatic transmissions, power steering, couple converters and other specific hydraulic applications.

APPLICATION: **BARDAHL MULTI ATF 7G** has an excellent stability and low temperature fluidity. Ideal for cold starts. It can be used in many automatic transmissions of different manufacturers and especially MERCEDES.

SPECIFICATIONS

The product meets the following performance levels:

WARNER JWS	3309 / 3324 / AW-1
ALLISON	C4
CHRYSLER	ATF+/+2/+3/+4
BMW	7045E/8072B/LA2634/LT71141/ATF3/3+/M-1375.4
FORD MERCON	ULV/LV/V/SP / WSS-M2C922-A1
GM DEXRON	ULV/VI/II/III/IV/VE/VII/VIII/IX/Suffix A
HONDA	DW-1/3.0/3.1/ATF-Z1 (except in CVT)
HYUNDAI/KIA	SP-II/III/IV/IV RR/RED-1K/NWS 9638
ISUZU	ATF II/III
JAGUAR	JLM 20238/20292/21044
JASO	M315 Type 1A LV
MAZDA	FZ/M-III/Type T-IV
MERCEDEZ	236.5/236.6/236.7/236.8/236.9/236.10/236.11/236.12/236.14/ 236.15/236.41
MINI	SP-II/III/J2/J3/PA
NISSAN	MATIC-D/J/K/S/W
SUBARU	ATF HP
SUZUKI	ATF 3314/3317
TOYOTA LEXUS	Type DII/T/T-III/T-IV/WS
VOLVO	1161540
VW	G 052 025/G 052 055/G 055 025/G 052 162/G 052 990/G 052 533/G 055 005/G 055 540/G 060 162
ZF	TE ML 11A/ 11B



PROPERTIES

- ✓ Very high viscosity index ensuring a high stability,
- ✓ Extended lifespan,
- ✓ Very low pour point,
- ✓ Very good thermal stability,
- ✓ Very good anti-oxidation protection,
- ✓ Anti-wear, anti-corrosion and anti-foam,
- ✓ High performance anti-friction additives,
- ✓ Safe for gaskets and non-ferrous metals,
- ✓ Offers a good resistance to vibration,
- ✓ Protects directly from cold start,
- ✓ High viscosity to prevent an over-consumption of fuel (fuel economy),
- ✓ Red color.

TECHNICAL DATA

Densité à 15°C	Kg/l	0,857
Viscosité -30°C	mPa.s	2980
Viscosité 40°C	mm ² /s	27,4
Viscosité 100°C	mm ² /s	6,37
Indice de Viscosité		197
Point d'éclair COC, °C	°C	146
Point d'écoulement, °C	°C	-57

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet. Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36581	12 x 1 L
36583	3 x 5 L
36588	20 L
36584	60 L
36587	205 L