



XTA Polar Plus

DESCRIPTION

XTA Polarplus is a Premium Quality lubricant for latest generation of gasoline and diesel engines equipped with exhaust gas after-treatment systems that require lubricants with low SAPS content (Sulfated Ash, Phosphorus and Zinc).

Thanks to its specific lowSAPS additives, with low sulfur, phosphorus and sulphated ash content, it allows to extend the lifespan of anti-particulate filters (FAP and DPF) and catalysts.

The top quality synthetic bases and the special high shear stability polymers employed in its formulation give XTA Polarplus extraordinary properties of thermal-oxidative resistance, tenacity of the lubricating oil film and fluidity at low temperatures.

XTA Polarplus also guarantees superior control of deposits, sludge and wear, allowing the maximum mechanical efficiency of the engine and maintaining its original performance over time.

XTA Polarplus helps to effectively counteract wear due to oil dilution with fuel and the accumulation of dirt in the engine resulting from the use of biodiesel.

SPECIFICATIONS

This product offers the following performance level:

ACEA	C3/C4
RENAULT	RN0720
MB	229.1/229.31/226.51

PROPERTIES

- ✓ Maximizes engine performance
- ✓ Low SAPS technology: low sulphated ash, phosphorus and sulfur content
- ✓ Greater longevity and cleanliness of all engine parts
- ✓ Easy start and immediate lubrication at low temperatures
- ✓ 100% Synthetic formula





TECHNICAL DATA SHEET V032021

TECHNICAL DATA

Viscosity at 40°C	67,6
Viscosity at 100°C	12,1
Viscosity Index	0,849
Viscosity at 40°C	178
Flash point	204,5
Pour Point	-42
T.B.N.	6,9

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

310040	24x1L
310053	60L
310054	200L



BARDAHL | *NOTHING WILL STOP YOU*

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers, 3 ZI TOURNAI Ouest, 2
T: (+32) (0) 69 59 03 60

www.bardahl.fr
www.bardahloils.com