

XTG CVT

DESCRIPTION

Very high-performance fluid formulated for Continuously Variable Transmissions (CVTs). Suitable for CVT chain and CVT belt.

APPLICATION

BARD AHL XTG CVT allows limiting fuel overconsumption on vehicles equipped with a CVT transmission.

SPECIFICATIONS

This product offers the following performance level:

| | |
|---------------------|---|
| BMW - Mini Cooper | EZL799 / EZL799A |
| MERCEDES | 236.20 |
| VW | G 052 180/ G 052 516 |
| NISSAN | NS-1/2/2V/3 / N-CVT |
| HONDA | HMMF (without starting clutch) / HCF2 / iIMMD |
| MITSUBISHI | SP-III (only CVT) / CVTF J1/(ECO)J4/J4+ |
| SUBARU | ECVT/iCVT/iCVT FG/NS-2 / Lineartronic High Torque (HT) CVTF / Lineartronic chain CVTF/CVTF II |
| DAIHATSU | AMIX CVTF DC/DFE / DFC |
| SUZUKI | CVTF TC / 3320 / 4401 / NS-2 / Green 1/2/1V |
| HUYNDAI | CVT-J1/ SPIII (CVT Model) |
| KIA | CVT-J1/ SPIII (CVT Model) |
| CHRYSLER JEEP DODGE | NS-2 / Mopar CVTF+4 |
| TOYOTA | CVTF TC / FE / THSII |
| FORD | WSS-M2C928-A / Hybrid e-CVT |
| MOPAR | CVTF+4 |
| MAZDA | JWS 3320 |
| GM | DEX-CVT / 1940713 / 1940714 |
| JATSO | CVT 8 Hybrid |



PROPERTIES

- ✓ Has a very low pour point,
- ✓ Has a very high and stable viscosity index,
- ✓ Performs well against friction,
- ✓ Provides antivibration performance,
- ✓ Extends the oil drain intervals,
- ✓ Provides a good resistance against oxidation and corrosion,
- ✓ Offers anti-wear, anti-foam, and anti-shudder properties.

TECHNICAL DATA

| | | |
|---------------------|--------------------|-------|
| Density at 20°C | Kg/l | 0,852 |
| Viscosity at 40°C | mm ² /s | 35,4 |
| Viscosity at 100°C | mm ² /s | 7,3 |
| Viscosity Index | | 177 |
| Flash point COC, °C | °C | 214 |
| Pour point, °C | °C | -42 |

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

| | |
|-------|----------|
| 36501 | 12 x 1 L |
| 36508 | 20 L |