



→ Workshop consumables



Silicone Lubricant

Ref. 4457B

12x300ml



USE

Bardahl **Silicone Lubricant** is particularly recommended for a long-lasting and clean lubrication. It can be applied on rubber, plastics, derivatives, wood, copper, aluminum,... Suitable for any support such as gaskets, rails, slides, sheaths, hinges,...

Can be used in automotive, motorbike, marine, DIY and any other domestic use.

PROPERTIES

Bardahl **Silicone Lubricant** has the following properties:

- Dry, clean and long-lasting lubricant,
- Resists water and protects against corrosion,
- Removes squeaking noise,
- Avoids frictions,
- Is an excellent electrical insulator,
- Improves sliding,
- Leaves an anti-static film,
- Protects the plastic against drying and discoloration,
- Protects the electrical components against oxidation,
- Resists temperatures from -20°C to +180°C.

INSTRUCTIONS FOR USE

Shake well before use. Carefully clean the supports, spray the product by using the extension pipe for a specific application and to reach difficult access.

PHYSICAL & CHEMICAL PROPERTIES

Physical state	Liquid
Boiling point	77 °C
Auto-ignition temperature	200 °C
Decomposition temperature	200 °C
Relative density	< 1 (20°C)
Viscosity, kinematic	< 7 mm ² /s (40°C)

V08/2019