



# XTEC 0W30

## DESCRIPTION

High performance 100% synthetic oil with low ash content developed to extend the lifespan and protect the efficiency of emission reduction systems on diesel and petrol vehicles.

## APPLICATION

**BARDAHL XTEC 0w30** has been developed according to the Mid S.A.P.S./low HTHS technology and can be used in any engine requiring a diesel or petrol engine oil with the Peugeot Citroën B71 2312 oil performance level.

## SPECIFICATIONS

This product offers the following performance level:

ACEA	C2
FIAT	9.55535-GS1/DS1 (C2)
PSA	B71-2312
FORD	M2C950-A

## PROPERTIES

- ✓ Avoids fuel overconsumption.
- ✓ Preserves the lubricating film at high temperature,
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Makes cold starting easier,
- ✓ Offers a high protection against oxidation.



## TECHNICAL DATA SHEET V032023

### TECHNICAL DATA

Density at 15°C	Kg/l	0,848
Viscosity at -35°C	mPa.s	5540
Viscosity at 40°C	mm <sup>2</sup> /s	53,6
Viscosity at 100°C	mm <sup>2</sup> /s	9,7
Viscosity index		168
Flash point COC, °C	°C	230
Pour point, °C	°C	-48
TBN alkalinity	mgKOH/g	6,2
Sulphated ash contents	%	0,59

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

### RECOMMENDATIONS

**Handling:** any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

**Storage :** it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

### REFERENCES & AVAILABILITIES

36521	12 x 1 L
36522	4 x 4L
36523	3 x 5 L
36528	1 x 20L
36524	1 x 60L
36527	1 x 205 L