

# ATF VI

## DESCRIPTION

High quality and high viscosity synthetic automatic fluid, formulated for automatic transmissions, power steering systems, torque converters and other hydraulic specific applications.

## APPLICATION

**BARDAHL ATF VI** provides an excellent stability and fluidity at low temperature. Ideal for cold starting and extended lifespan. Bardahl ATF VI can be used when an ATF fluid showing superior performance to Dexron II and III is recommended. **CAUTION: Bardahl ATF VI CANNOT BE USED IN CVT AND DCT TRANSMISSIONS, or when the FORD Type F/G performance level is required.**

## SPECIFICATIONS

This product offers the following performance level:

AISIN WARNER	JWS 3309(T-IV)/3324(WS)/AW-1/AW-2
ALLISON	C3/C4
BMW	7045E/8072B/LA2634/ATF6/Mini
CAT	TO-2
CHRYSLER DODGE MOPAR	AS68RC/69RC (T-IV)
CHRYSLER	ATF+/-2/+3
FIAT	Type IV/9.55550-AV5/AV-6
DAIHATSU	ATF D-II/D-III SP
FORD	Mercon/LV/M2C138-CJ/166-H/922-A1/924-A/938-A
GM DEXRON	VI/II/IID/IIIE/IIIG/IIIH
TASA	Type A Suffix A
HONDA	Acura DW-1/ATF-Z1(except in CVT)
HYUNDAI/KIA	SP-II/SP-III/SP-IV/SP-IV M/SP-IV RR
JAGUAR	ATF 3403 M115/JLM 20238/20292
JASO	M315-2013 1A/1A-LV/2A
MAZDA	ATF DII/M-III/M-V/FZ/A7/F-1/S-1/N-1/3317
MB	236.1/2/3/236.5/236.7/236.8/236.9/236.41
MITSUBISHI	SK/SP-II/SP-III/SP-IV/AW/J2/J3/ PA/MA1
NISSAN	Matic C/D/J/K/P/S/W
PORSCHE	3403-M115/T-IV
SUBARU	ATF/5AT/HP
SUZUKI	ATF 3309/3314/3317/2326/2384K
PSA	B71 2340
TOYOTA	D-II/D-III/T-III/T-IV/WS
TESLA	Model S/3/X
VW	G 052 025 / G 052 055 / G 052 162 / G 052 990 / G 053 001 / G 053 025 / G 055 005 / G 055 025 / G 055 162 / G 055 540 / G 060 162
VOITH	55.6335.xx (G607)
VOLVO	97335/97340/1161540
ZF	5HP 18FL/19FL/24A/30/4HP20
ML	05L/09/11A/B/21L



## PROPERTIES

- ✓ Has a high viscosity index ensuring a very good stability,
- ✓ Extended lifespan,
- ✓ Has a very low pour point,
- ✓ Offers an excellent stability at different temperatures,
- ✓ Offers a very good protection against oxidation,
- ✓ Provides anti wear, anticorrosion and antifoam properties,
- ✓ Contains antifriction additives,
- ✓ Does not damage synthetic gaskets and non-ferrous metals,
- ✓ Circulates quickly at cold start,
- ✓ Yellow color.

## TECHNICAL DATA

Density at 15°C	Kg/l	0,845
Viscosity 40°C	mm2/s	29,6
Viscosity 100°C	mm2/s	5,90
Viscosity Index		149
Flash point COC, °C	°C	212
Pour point, °C	°C	-48

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

## RECOMMENDATIONS

**Handling :** any safety information related to the handling and use of this product are gathered in the Safety Data Sheet. Always check the manufacturer car manual before use.

**Storage :** it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

## REFERENCES & AVAILABILITIES

36591	12 x 1 L
36593	3 x 5 L
36598	20 L
36594	60 L
36597	205 L