



XTRA 10w40

DESCRIPTION

Universal semi-synthetic multigrade lubricant for petrol and diesel engines (without DPF), turbo-charged or not.

APPLICATION

BARDAHL XTRA 10w40 is formulated from the last generation technology. Can be used in passenger car and duty vehicle engines.

SPECIFICATIONS

This product offers the following performance level:

ACEA	A3/B3
API	SL/CF
VW	501.01/505.00
MERCEDES-BENZ	MB 229.1

PROPERTIES

- ✓ Offers a stable viscosity
- ✓ Forms a lubricating film protecting the engine at high temperature,
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Makes cold starting easier,
- ✓ Provides a high protection against corrosion, wear and the formation of foam.



TECHNICAL DATA

Density at 15°C	Kg/l	0,846
Viscosity at -25°C	mPa.s	<6800
Viscosity at 40°C	mm ² /s	85
Viscosity at 100°C	mm ² /s	14
Viscosity Index		164
Flash point COC, °C	°C	234
Pour point, °C	°C	-36
TBN Alkalinity	mgKOH/g	10,1
Sulphated Ash contents	%	1,29

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

34133	3 x 5 L
34137	205 L