



# XTEC TRUCKS 15W40

## DESCRIPTION

Synthetic oil made from last generation performance additives and formulated for Euro V and VI heavy diesel engines (trucks, buses and delivery vans) to reduce friction, eliminate sludge and optimize fuel consumption. It is based on the LOW SAPS (very low ash contents) technology to ensure an extended lifespan and a good functioning of post-treatment exhaust systems (DPF).

## APPLICATION

**BARDAHL XTEC Trucks 15w40** provides an excellent stability and a high resistance to temperatures to avoid the formation of deposits, and makes cold start easier. Compatible with EGR, SCR, DPF, Low S diesel.

## SPECIFICATIONS

This product offers the following performance level:

ACEA	E7, E9, E11
API	CK-4/ SN
MB	228.31
RENAULT VI	RLD-3
DEUTZ	DQC III-18 LA
VOLVO	VDS-4.5
MACK	EOS-4.5
MAN	M3775
FORD	WSS M2C171-F1
MTU	Type 2.1
CUMMINS	CES 20086
CAT	ECF-3
DETROIT DIESEL	93K222
ALLISON	TES-439
DTFR	15C100
JASO	DH-2



## PROPERTIES

- ✓ Makes cold start easier,
- ✓ Helps to extend the lifespan of particle filters,
- ✓ Offers high detergency properties and avoids the formation of deposits,
- ✓ Provides a very good protection against shearing,
- ✓ Provides strong dispersion properties,
- ✓ Is highly resistant against corrosion and oxidation,
- ✓ Decreases wear and avoids the formation of foam,
- ✓ Has a low ash contents.

## TECHNICAL DATA

Density at 15°C	Kg/l	0,874
Viscosity at -25°C	mPa.s	6480
Viscosity at 40°C	mm <sup>2</sup> /s	113
Viscosity at 100°C	mm <sup>2</sup> /s	14,9
Viscosity Index		137
Flash point COC, °C	°C	222
Pour point, °C	°C	-36
TBN alcalinity	mgKOH/g	8,1
Sulphated ash contents	%	0,9

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

## RECOMMENDATIONS

**Handling :** any safety information related to the handling and use of this product are gathered in the Safety Data Sheet. Always check the manufacturer car manual before use.

**Storage :** it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

## REFERENCES & AVAILABILITIES

36368	20 L
36364	60 L
36367	205 L



**NOTHING WILL STOP YOU**

SADAPS BARDAHL ADDITIVES & LUBRICANTS  
Rue du Mont des Carliers,3, ZI Tournai Ouest II  
T: (+32) (0) 69 59 03 60

www.bardahl.be  
www.bardahloils.com